

Snell Premier Series IC-D7

FOR BUILT-IN CABINETS, A UTILITY VERSION OF THE ACCLAIMED D7 TOWER


The unique cabinet design, placement switch and wide dispersion tweeter of the IC D7 bring the performance of a freestanding high-end tower to an in-cabinet bookshelf enclosure. Conventional bookshelf loudspeakers sound "chesty" and image poorly when used in in-cabinet applications. The IC D7 is a 6.5-inch, D'Appolito Array, designed by Snell chief engineer, Joe D'Appolito, to fit into furniture and millwork, and, is tuned to compensate for the sonic problems that these cabinet boundaries cause. The twin 6.5-inch long throw woofers provide extended bass and plenty of output, while the 1-inch low-resonance, silk dome tweeter enables a large sweet spot for better stereo imaging. The IC D7 uses the same components as the Snell D7 Tower and IW D7 in-wall monitor, mounted in a robust, texture-painted enclosure. This high output LCR can be used for Left, Center and Right or mixed and matched with these two siblings to provide clean, impactful sound with an effortless and "airy" soundstage... perfect for music and movies.



Dimensions:


• 19.5" Wide • 7.75" High • 11" Deep

Application Alternatives:



D7 In Room

System Suggestions:



IC Basis 300 Sub

SR7 Surround

Like all Snell loudspeakers, each IC-D7 is hand tuned for natural imaging and sonic depth.

Design:
Acoustic Suspension
D'Appolito array

Frequency Response
62Hz-20kHz ± 3dB

Sensitivity
[1Watt (2.83v) @ tm]
90 dB

Impedance
Nominal 4 Ohms

Maximum Output
110 dB

Recommended Power
50 Watts minimum
250 Watts maximum

Tweeter
1-inch SEAS silk dome

Woofer
Two 6.5-inch Copolymer cone,
6mm Excursion

Crossover Frequency
2.2 kHz

Crossover
Discrete tweeter, and woofer
circuit boards. Time alignment
and coherency are achieved
through the transition region from
driver to driver. Each crossover is
individually tuned by our
technicians to ± 0.5db of the
Master Reference.

Boundary compensation
"Normal" – When placed on
stands away from wall.

"Boundary" – When placed on
shelf or near wall.

Wiring
Bi-amp, bi-wire ready

Connections
5-way satin, nickel-plated, brass
terminals, accepts 5/16 - inch
spades, pins, banana plugs and
bare wire to 12 gauge.

Cabinet Construction
Hardwood veneer over 3/4-inch
MD Panels. 3/4 -inch textured
painted.

Grille
Black cloth over MDF frame.

Finishes
Textured black paint. Can
be ordered in most wood
and paint finishes.

Weight
30 lbs.



Manufactured in the USA by Snell Acoustics, Peabody MA 01960 • www.snellaoustics.com • 978-538-6262 • © Snell Acoustics, Inc • All specifications subject to change without notice.

Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>