
HOTSOAK 50





HOTSOAK SERIES MODEL # AI7242RHS














SPECIFICATIONS:

GENERAL SPECIFICATIONS:

Tub Size 71 1/2" x 42 3/16" x 23 1/4"

182 cm x 107 cm x 59 cm

Bathing Well 43" long

24" wide

22" interior depth

Shipping Weight 247 lbs. / 112 kg Tub Weight Filled 877 lbs. / 398 kg Tub Only Weight 154 lbs. / 70 kg

Tub Only Weight 154 lbs. / 70 kg Gallons to Overflow 90 gal. / 341 L

ELECTRICAL SPECIFICATIONS:

 Pump
 1/15 HP; 1.3 AMP; 110V

 Heater
 1.5 kW; 12.5 AMP; 110V

 Requirements
 20 AMP; 110V, separate circuit

required protected w/ Class A GFCI

STANDARD EQUIPMENT:

Aquatic Quality Features:

- Run-Dry Pump with 20-Minute Timer
- 1.5 kW Inline Maintenance Heater
- 2 Circulation Portal Covers
- Bath-Side On/Off Electronic Button
- "Quiet Pad" Anti-Vibration Pump Mount for Quiet Operation
- Color Matched Grab Bar
- 4 Arm Rests
- Slip Resistant Floor
- Pre-leveled ABS Support Base
- Heat-bent Rigid PVC Piping for Optimum Sanitary Conditions
- Durable, Easy to Clean, Lucite® Cast Acrylic Surface
- Available in 8 Standard No-Charge Colors

UL & IAPMO Listed, Factory Tested Limited Lifetime Warranty

OPTIONAL EQUIPMENT:

- · Chromatherapy LED Lighting*
- · Comfort Pillow Oval or Rectangle
- Grab Bar
 - White, Biscuit, Chrome, Polished Brass, Gold, Polished Nickel, Satin Nickel or Oil Rubbed Bronze
- Lift & Turn Waste and Overflow
 - Chrome, Polished Brass, Gold, Polished Nickel, Satin Nickel or Oil Rubbed Bronze
- Cable Drive Waste and Overflow
 - Chrome, Polished Brass, Gold, Polished Nickel, Satin Nickel, Oil Rubbed Bronze or Color Matched (Bone, White and Biscuit Only)
- Factory Installed Rigid ABS Tile Flange
- Optional Pump Location
- Color Matched Acrylic Skirt
- Premium Colors

All acrylic colors featured by Aquatic match the industry's leading fixture manufacturers.

*This whirlpool will need to be hard wired to the breaker box. Three outlets will be supplied on the whirlpool.

Fax-On-Demand Document #1225

96



The manufacturer accepts a 1/4" variance. There are variations on each tub and specifications are subject to change as we improve upon our product as required. The dimensions needed for site preparation and structure building should be measured from the tub; Aquatic Industries, Inc. assumes no responsibility for preparatory work.

800.555.5324

Free Manuals Download Website

http://myh66.com

http://usermanuals.us

http://www.somanuals.com

http://www.4manuals.cc

http://www.manual-lib.com

http://www.404manual.com

http://www.luxmanual.com

http://aubethermostatmanual.com

Golf course search by state

http://golfingnear.com

Email search by domain

http://emailbydomain.com

Auto manuals search

http://auto.somanuals.com

TV manuals search

http://tv.somanuals.com