

B-CONTROL ▶ DEEJAY BCD2000

Technical Specifications

GB

Version 1.0 June 2005



www.behringer.com



B-CONTROL ► DEEJAY BCD2000

The Ultimate DJ Machine—Play, Mix and Scratch any MP3 and WAV Files just like Vinyl Records

GB

- ▲ Play, mix and scratch any MP3 and WAV files just like vinyl records with ultra-low latency
- ▲ Full-speed USB 4-channel audio interface plus high-resolution 24-bit A/D and D/A converters
- ▲ Perfectly complements the included BEHRINGER B-DJ software or any other DJ software
- ▲ 2 scratch wheels support creative DJing such as scratching, pitch bending and cue searching
- ▲ Full-fledged DJ mixer control panel with premium quality mic preamp, 3-band kill EQ per channel, ultra-precise faders, super-smooth crossfader and talkover function
- ▲ 2 state-of-the-art phono preamplifiers—one switchable to CD player
- ▲ Sophisticated headphone section includes PFL Mix, Split options and direct listening to master output mix
- ▲ Play, Pause, Cue, Loop and Pitch Bend functions via dedicated controls for intuitive DJing
- ▲ 4 user-assignable controls and buttons available for integrated FX section
- ▲ Innovative Cue logic with multiple storable cue points per song
- ▲ High-quality components and exceptionally rugged construction ensure long life
- ▲ Conceived and designed by BEHRINGER Germany

BCD2000



SPECIFICATIONS

AUDIO INPUTS

Microphone input

Type	XLR balanced
Gain range	-∞ - +50 dB
Frequency response	10 Hz - 29 kHz (-3 dB)
Impedance	approx. 2 kΩ (balanced)
Max. input level	-25 dBu @ 35 dB Gain (mic level center position)
Signal-to-noise ratio	110 dB (A-weighted)
Distortion (THD+N)	0.01 % (A-weighted)
CMRR	typ. -40 dB
Equalizer	
EQ low	±12 dB @ 40 Hz
EQ high	±12 dB @ 12 kHz

Line inputs

Phono in	40 dB Gain
Line in	0 dB Gain
Impedance	approx. 47 kΩ
Max. input level	+12 dBu

AUDIO OUTPUTS

Master Out

Type	RCA
Impedance	120 Ω
Signal-to-noise ratio	101 dB
Crosstalk	<80 dB @ 1 kHz
Max. output level	+18 dBu

Phones Out

Type	1/4" TRS connector
Max. output level	+4.7 dBu (+18.2 dBm) @ 30 Ω loading

DIGITAL PROCESSING

Converter	24 Bit
Sample rate	44.1 kHz
Signal-to-noise ratio	A/D: 100 dB D/A: 100 dB

USB INTERFACE

Type	Full-Speed 12 MBit/s
------	----------------------

SYSTEM SPECIFICATIONS

Signal-to-noise ratio	>80 dB
Crosstalk	<80 dB
Distortion (THD)	0.01%
Frequency response	15 Hz - 21 kHz, +0/-3 dB

POWER SUPPLY

Voltage	100 - 240 V~, 50/60 Hz
Power consumption	max. 7 W
Fuse	T 1 A H 250 V
Mains connection	Standard IEC receptacle

DIMENSIONS/WEIGHT

Dimensions (W x H x D)	13" x 3.9" x 11.8" (330 mm x 100 mm x 300 mm)
Weight	approx. 4.41 lbs (2.0 kg)

BEHRINGER is constantly striving to maintain the highest professional standards. As a result of these efforts, modifications may be made from time to time to existing products without prior notice. Specifications and appearance may differ from those listed or illustrated.

Technical specifications and appearance subject to change without notice. The information contained herein is correct at the time of printing. The names of companies, institutions or publications pictured or mentioned and their respective logos are registered trademarks of their respective owners. Their use neither constitutes a claim of the trademarks by BEHRINGER® nor affiliation of the trademark owners with BEHRINGER®. BEHRINGER® accepts no liability for any loss which may be suffered by any person who relies either wholly or in part upon any description, photograph or statement contained herein. Colours and specification may vary slightly from product. Products are sold through our authorised dealers only. Distributors and dealers are not agents of BEHRINGER® and have absolutely no authority to bind BEHRINGER® by any express or implied undertaking or representation. No part of this manual may be reproduced or transmitted in any form or by any means, electronic or mechanical, including photocopying and recording of any kind, for any purpose, without the express written permission of BEHRINGER Spezielle Studiotechnik GmbH. BEHRINGER® is a registered trademark.

ALL RIGHTS RESERVED. © 2005 BEHRINGER Spezielle Studiotechnik GmbH,
Hanns-Martin-Schleyer-Str. 36-38, 47877 Willich-Münchheide II, Germany.
Tel. +49 2154 9206 0, Fax +49 2154 9206 4903

Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>