



Unique Brother Features

Enhance your productivity with Brother's FAX-236S – a direct thermal fax machine that is ideal for confidential documents as received messages will not remain on the thermal ribbon after fax receptions.

With FAX-236S, document clarity can be improved with the "Smoothing" Enhanced Image Resolution, which softens jagged edges around text. FAX-236S is equipped with an Anti-Curl System (ACS) that flattens paper and prevents it from curling. It also comes with Automatic Fax/Tel Switch, where faxes are automatically received without having to press the START key, upon picking up the handset.

FAX-236S has a Key Lock System that prohibits receiving faxes or answering calls, unless a 4-digit password is activated. This prevents unauthorised access to the fax machine. Furthermore, junk faxes and calls can be screened out with the handy Anti-Junk Function* that prevents paper wastage, by saving only authorised numbers in the station's memory. For more storage of numbers, up to 100 speed-dial locations can be saved!

Brother's FAX-236S truly delivers an easy-to-use and space saving solution to meet all your facsimile needs.

Specifications

General

Print Engine	Direct Thermal
Modem Speed	9.6K bps, approximately 15 sec**
ITU-T Group / Coding Method	G3 / MH
Input/Output Width	A4
Automatic Document Feeder	Up to 10 pages
Automatic Paper Cutter	Yes
Anti Curl System	Yes
Starter Paper	8m
LCD Size	16 characters x 1 line
On-Screen Programming	Yes
Back up Clock	Up to 48 hours

Telephone

Automatic Redial	Yes
Handset	Yes
One-Touch	Up to 4 stations
Speed Dial	Up to 100 locations
Tel-Index	Yes
Chain Dialing	Yes
Caller ID*	Yes
Caller ID Log*	Yes - Up to 10
Call back by using stored caller ID*	Yes
Registration of Caller ID Information*	Yes - One Touch and Speed Dial
Distinctive Ringing*	Yes
Hold/Mute Key	Yes - Music on Hold
Night Mode	Yes
Semi-Dect Management	Yes
Key Lock System	Yes

* Please check with your local phone company for the availability of these services.

** Based on Brother Chart at Standard Resolution

Contact:

Brother International Corporation, Nagoya Japan

All specifications correct at time of printing. Brother is a registered trademark of Brother Industries Ltd. Brand product names are registered trademarks of their respective companies.

www.brother.com

List/Report

Activity Report/Journal Report	Yes - Up to 15
Transmission Verification Report	Yes
Cover page	Yes
Help List	Yes
Call Back Message	Yes
Caller ID List	Yes

Fax

Easy Receive/Fax Detect	Yes
Automatic Fax/Tel Switch	Yes
Super Fine	Yes
Gray Scale	64 (Dithered)
Contrast	Light/Auto/Dark
Smoothing	Yes
Call Reservation	Yes
Enhanced Remote Activation	Yes
Multi Resolution Transmission	Yes
Next-Fax Reservation	Yes
Delayed Timer	1 Timer
Polling Type	Yes - Sta/Del/Sec

Copy

Copy Resolution	Up to 203 x 392dpi
-----------------	--------------------

Dimensions and Weight

Dimensions (W x D x H)	299 x 240 x 137mm
Weight	2.9kg

Optional Accessories and Consumables

CT-70 Catch Tray	For neat stacking of original documents
Standard Thermal Paper Size	50m
Therma PLUS Paper Size	30m

Brother strongly recommends the use of Genuine Brother consumable products only. Benefits include better quality prints, greater yields per consumable, protection of your machine from damages and achievement of optimum performance. As a precaution, please note that your machine warranty may not cover any damages arising from the use of non-genuine Brother consumables.



FAX-236S
Stay Connected
with Brother's Latest Direct Thermal Facsimile



Key-Lock System



Night Mode



Caller ID



Automatic Paper Cutter



Anti-Junk Function

Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>